

5" Rugged Android Computer

The Unitech EA600 (Android) is a rugged 5" mobile enterprise computer combining strong features with powerful data collection. The EA600 provides convenient connectivity, reading capabilities and enhances the service level for a variety of vertical applications within the retail, transport, logistics and field service sectors.



Competitive all-in-one package.

The EA600 (2D / 3G / Dual-band WiFi) comes standard with charging cradle (includes a battery charging slot) and power supply!

Powerful data collection

Equipped with an 1.2GHz Quad-Core processor and running on the Android 5.1 operating system, make this device suitable for data-intensive applications in highly mobile environments. Mobile workers can easily accelerate their workflow as this device is equipped with a 2GB RAM, 8GB ROM and supporting an additional microSD expansion (up to 32GB storage capacity).

All-in-one Functionality

The EA600 offers an integrated 2D scanning capability, as well as an integrated HF/NFC RFID reader/writer, GPS and a high resolution 8.0 MP camera.

Holding a 4000mAh removable battery the EA600 provides continuous usage time without needing to worry about running out of juice. This device offers everything you'll need. By supporting a PSAM slot, the EA600 meets the requirements of financial institutions and government agencies.

Enjoy the fastest data speeds out there with the integrated Bluetooth 4.0, Dual-band 802.11 a/b/g/n WiFi and 3G connectivity. This device is truly an excellent mobility device and offers improvement of job efficiency at a competitive price!

Rugged design

C Capable to withstand a multiple 1.5m drops to concrete and IP65 rated against water and dust, makes this EA600 a rugged device. Equipped with a POGO PIN (for quick and non-intrusive charging) it will prolong it life span and durability.

Industrial grade & sensitivity design.

This all-in-one solution package empowers your mobile workforce - where realtime data collection is critical.

Main features

- All-in-one box; EA600 comes with USB cradle and power supply.
- All-in-one function: 2D Imager, HF/NFC and 8MP Camera.
- Industrial grade: 1.2GHz Quad-Core processor with Android 5.1 OS
- Suitable for any mobile worker: 3G (4G coming soon), Dual-Band 802.11 a/b/g/n WiFI, GPS and Bluetooth 4.0 HS slow energy.
- Enhanced security by preventing 3rd party data collection (without GMS).
- Rechargeable and swappable 4000mAh battery.
- 5" HD display. Ultra sensitive capacitive touch screen (compatible with gloves and supports wet resistance).
- Rugged: Gorilla Glass 3, IP65 rated and 1.5m drop specification.
- Dual Scanning Buttons (left and right side) and programmable key.
 Device supported versatile: SOTI, 12Manage and MoboLink
- Optional additional UnitCare 2.0 coverage available.







V1.1 EA600 Specifications

Operation System

CPU 1.2GHz, Qualcomm 8916 Quad-Core

Memory 2GB DDR RAM

8GB ROM

OS Android 5.1

Enhanced security by preventing 3rd party data

collection (without GMS).

Languages Multi-language

Others Input Chinese/ English, supports handwriting

and soft keyboard.

Display

5.0 inch TFT-LCD HD (720 \times 1280) color screen, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

Buttons

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button.

Camera/Photos/Video

2MP front camera

8MP rear camera with LED flash and auto-focus function

Indicator

LEDs, Vibrator

Symbologies2D CMOS Imager

1D/2D All major 1D and 2D codes

RFID

HF/NFC Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693 standard,

Supports NFC

Communication

USB Micro USB

OTG Yes, over Micro USB

POGO PIN Charging via cradle and USB client

WLAN 802.11 a/b/g/n

Bluetooth Bluetooth 4.0 HS low energy

WWAN GSM/HSDP+/UMTS,

4G (coming soon)

GPS GPS, AGPS, Glonass

Senors Proximity sensor, light sensor and G-sensor

Power Source

Operation time

Main battery Rechargeable and swappable

3.8 V, 4000mAh Polymer Li-ION pack. 10-12 hours (depending on the specific

environment)

RTC battery Real time clock battery

Audio

Microphone, speaker and 3.5mm audio jack

Expansion Slot

Micro SD/TF x 1(maximum of 32 GB), Micro SIM x 1, SAM x 1

Enclosure

Dimension 152 mm x 78 mm x 15 mm

Weight 283g

Environmental

Operating temperature -10°C to +50°C
Storage temperature -20°C to +60°C
Charging Temperature 0°C to 40°C

Relative Humidity 5% ~ 95% (non-condensing)

Drop Specification 1.5m to concrete

Sealing IP65

Accessories

Single slot USB cradle



EA600 1-Slot Charging USB Cradle

1-slot USB cradle with spare battery charging compartment

Input: AC 100V~240V,1A Max,50/60Hz

Output: DC 5.5V,2.6A Led: Power and Status

Regulatory Approvals

CE, R&TTE

Device supported MDM

SOTI, 12Manage and MoboLink

Warranty

1 Year Terminal and cradle / 3 months battery.



Unitech's service program

UnitCare 2.0 offers customers a high level of security by a reliable, high-quality and effective program for getting your devices serviced quickly. It also drives the hidden costs out of your installations. UnitCare goes beyond the standard warranty with a complete service offer for different need. **More information: unitcare.unitech.eu**.



Tilburg, The Netherlands

- Tel.: +31 (0)13 460 9292
- Email: Info@eu.ute.com
- Website: http://eu.ute.com
 Unitech America



Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

unitech

because we care

Specifications subject to change without notice. Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.