



EA602

5" Rugged Android 7.1 Computer

The Unitech EA602 (Android 7.1) is a rugged 5" mobile enterprise computer combining strong features with powerful data collection. The EA602 provides convenient connectivity, reading capabilities and enhances the service level for a variety of vertical applications within the retail, transport, logistics and field service sectors.



Competitive all-in-one package.
The EA602 (2D / 3G / 4G / LTE / Dual-band WiFi) comes standard with charging cradle (includes a battery charging slot) and power supply!

Powerful data collection

Equipped with an MSM8937 Octa-Core 1.4GHz processor and running on the Android 7.1 operating system, make this device suitable for data-intensive applications in highly mobile environments. Mobile workers can easily accelerate their workflow as this device is equipped with a 2GB RAM, 16GB ROM and supporting an additional microSD expansion (up to 32GB storage capacity).

All-in-one Functionality

The EA602 offers an integrated high performance (Honeywell N6603) 2D scanning capability, as well as an integrated HF/NFC RFID reader/writer, GPS and a high resolution 8.0 MP camera.

Holding a 4000mAh removable battery the EA602 provides continuous usage time without needing to worry about running out of juice. This device offers everything you'll need. By supporting a PSAM slot, the EA602 meets the requirements of financial institutions and government agencies.

Enjoy the fastest data speeds out there with the integrated Bluetooth 4.0, Dual-band 802.11 a/b/g/n WiFi and 4G/LTE connectivity. This device is truly an excellent mobility device and offers improvement of job efficiency at a competitive price!

Rugged design

Capable to withstand a multiple 1.5m drops to concrete and IP65 rated against water and dust, makes this EA602 a rugged device. Equipped with a POGO PIN (for quick and non-intrusive charging) it will prolong its life span and durability.

Industrial grade & sensitivity design.
This all-in-one solution package empowers your mobile workforce - where realtime data collection is critical.

Main features

- All-in-one box; EA602 comes with USB cradle and power supply.
- All-in-one function: High performance 2D Imager (Honeywell N6603), HF/NFC and 8MP Camera.
- Industrial grade: MSM8937 Octa-Core 1.4GHz processor with Android 7.1 OS
- Suitable for any mobile worker: 3G / 4G / LTE, Dual-Band 802.11 a/b/g/n WiFi, GPS and Bluetooth 4.0 HS slow energy.
- Enhanced security by preventing 3rd party data collection (without GMS).
- Rechargeable and swappable 4000mAh battery.
- 5" HD display. Ultra sensitive capacitive touch screen (compatible with gloves and supports wet resistance).
- Rugged: Gorilla Glass 3, IP65 rated and 1.5m drop specification.
- Dual Scanning Buttons (left and right side) and programmable key.
- Device supported versatile: SOTI, 12Manage and MoboLink
- Optional additional UnitCare 2.0 coverage available.

unitech
because we care



V1.3 EA602

Specifications

Operation System

CPU	MSM8937 Octa-Core 1.4GHz
Memory	2GB DDR RAM 16GB ROM
OS	Android 7.1
Languages	Multi-language
Others	Input Chinese/ English, supports handwriting and soft keyboard.

Display

5.0 inch TFT-LCD HD (720 x 1280) color screen, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

Buttons

Side SCAN button x 2 (Left / Right), User-defined function button (programmable key), Volume switch button (+ / -), ON / OFF button.

Camera/Photos/Video

2MP front camera
8MP rear camera with LED flash and auto-focus function

Indicator

LEDs, Vibrator

Symbologies

2D High Performance N6603

1D/2D All major 1D and 2D codes

RFID

HF/NFC

Frequency 13.56MHz
Support: ISO14443A/B, ISO15693 standard,
Supports NFC

Communication

USB	Micro USB
OTG	Yes, over Micro USB
POGO PIN	Charging via cradle and USB client
WLAN	802.11 a/b/g/n
Bluetooth	Bluetooth 4.0 HS low energy
WWAN	2G: 2G(GSM), 2G(GSM), 2G(CDMA) GSM/EDGE/GPRS (850,900,1800MHz) 3G: 3G(WCDMA), 3G (CDMA2000), 3G(TD-SCDMA) UMTS/HSDPA/HSPA/HSPA+ (850,900,2100MHz) CDMA EV-DO Rev.A (800MHz) Band 34,39 4G: 4G(TD-LTE), 4G(FDD-LTE), 4G(FDD-LTE) TDD-LTE (B38, B39, B40, B41) FDD-LTE (B1, B3, B7, B8) Proximity sensor, light sensor and G-sensor
Sensors	

Power Source

Main battery	Rechargeable and swappable 3.8 V, 4000mAh Polymer Li-ION pack.
Operation time	10-12 hours (depending on the specific environment)
RTC battery	Real time clock battery

Audio

Microphone, speaker and 3.5mm audio jack

Expansion Slot

Micro SD/TF x 1(maximum of 32 GB), Micro SIM x 1, SAM x 1

Enclosure

Dimension	152 mm x 78 mm x 15 mm
Weight	283g

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20°C to +60°C
Charging Temperature	0°C to 40°C
Relative Humidity	5% ~ 95% (non-condensing)
Drop Specification	1.5m to concrete
Sealing	IP65

Accessories

Single slot USB cradle
4-slot charging cradle
Vehicle cradle
Protection boot with handstrap and stylus.

1-Slot Charging USB Cradle

1-slot USB cradle with spare battery charging compartment



Input:	AC 100V~240V, 1A Max, 50/60Hz
Output:	DC 5.5V, 2.6A
Led:	Power and Status

*Spare battery not included.



4-slot Cradle



Vehicle Cradle



Protection boot

*EA602 not included.

Regulatory Approvals

CE, R&TTE

Device supported MDM

SOTI, 12Manage and MoboLink

Warranty

1 Year Terminal and cradle / 3 months

Unitech Europe

Tilburg, The Netherlands

•Tel.: +31 (0)13 460 9292

•Email: Info@eu.ute.com

•Website: http://eu.ute.com



Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

Specifications subject to change without notice. Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.



unittech
because we care